

## FiMoDeAL: pilot study on shortest path heuristics in wireless sensor network for fire detection and alert ensemble

Maureen Ifeanyi Akazue<sup>1</sup>, Abel Efetobor Edje<sup>1</sup>, Margaret Dumebi Okpor<sup>2</sup>, Wilfred Adigwe<sup>3</sup>, Patrick Ogholuwaremi Ejeh<sup>4</sup>, Christopher Chukwufunaya Odiakaose<sup>4</sup>, Arnold Adimabua Ojugo<sup>5</sup>, Edim Bassey Edim<sup>6</sup>, Rita Erhovwo Ako<sup>5</sup>, Victor Ochuko Geteloma<sup>5</sup>

<sup>1</sup>Department of Computer Science, Delta State University Abraka, Delta State, Nigeria

<sup>2</sup>Department of Cybersecurity, Delta State University of Science and Technology Ozoro, Delta State, Nigeria

<sup>3</sup>Department of Computer Science, Delta State University of Science and Technology Ozoro, Delta State, Nigeria

<sup>4</sup>Department of Computer Science, Dennis Osadebey University, Asaba, Nigeria

<sup>5</sup>Department of Computer Science, College of Computing, Federal University of Petroleum Resources Effurun, Delta State, Nigeria

<sup>6</sup>Department of Computer Science, University of Calabar, Calabar, Nigeria

### Article Info

#### Article history:

Received Dec 24, 2023

Revised Mar 7, 2024

Accepted Mar 28, 2024

#### Keywords:

Bellman ford algorithm

Dijkstra algorithm

Fire detection and response

Fire monitor

Internet of things

Wireless sensor networks

### ABSTRACT

With the incessant outbreak of fire, the heavy loss to both lives and properties in the society fire has since become a critical issue and challenge that needs our daily attention to be resolved. Loss of lives and properties to fire outbreak in 2021 alone as occurring in major Nigerian markets and residential homes was estimated at over 3 trillion Naira. Our study proposes a wireless sensor network internet of things (IoT) based ensemble to aid the effective monitoring, detection and alerting of residents and fire service departments. With cost as a major issue and the requisite installation of fire and smoke detectors in many houses our ensemble can efficiently integrate into the existing system using the ESP8285-controller to create a comprehensive access control system. The system provides real time monitor and control capabilities that will allow administrators to track and manage fire monitor and detection within a facility. Thus, enhances system's efficiency and performance.

This is an open access article under the [CC BY-SA](#) license.



### Corresponding Author:

Arnold Adimabua Ojugo

Department of Computer Science, College of Computing

Federal University of Petroleum Resources Effurun

Delta State, Nigeria

Email: ojugo.arnold@fupre.edu.ng

## 1. INTRODUCTION

Fire as an entity, has birthed significant industrial and technological growth with advances in the field of informatics and, remains a threat that must be addressed [1], [2]. Unfortunately, the rise in trend of fire outbreaks has since become a societal menace today leaving the loss to lives and property on it is wake [3]. Smoke, as associated with fire sucks all air and quickly render unconscious persons in it is immediate environ, leaving them with little or no time to escape [4]. With plenty synthetic materials rippled across our homes today [5]–[7], these elements yield hazardous compounds that increases the danger of fires and as the fire spreads it consumes available oxygen and releases toxic fumes from the incomplete combustion [8]–[11].

The havoc wreaked by it has become major concern as inhaled smoke has been a major cause of fire-related deaths [12]. Thus, birthing fire detection system, which automatically detect fire yielding an early alert protocol for occupants therein a building or otherwise of the existence and imminent threat/dangers of fire. There are a variety of communication mode for wireless sensor devices known as internet of things (IoT) based devices and these includes: i) device-to-device allows the device to interact directly with networks so that the

devices functions as intended using protocols such as Bluetooth, Z-Wave, and ZigBee enable direct communication between them. Many home automation systems uses this architecture [13], [14]; ii) device-to-cloud uses a cloud service provider to directly connect an IoT device and allow data exchange using pre-existing communication channels such as WiFi or wired Ethernet [15]–[17]; iii) device-to-gateway links an IoT device to a cloud service using an ALG service as a conduit, which implies the application software running on a local gateway device that serves as a bridge between the device and the cloud service and offers security and other features like data or protocol translation [18], [19]; and iv) backend data-sharing mode enables users to export and combine data from external sources with smart object data from a cloud service for analysis. It supports a user's view to grant other parties access to retrieved records in it is evolution of the single device-to-cloud comms paradigm, which may lead to data silos if an IoT device uploads data only to a single app service provider. Data collected from a single IoT device stream may be aggregated and analyzed [20]–[22].

The audible or visual alarm provided by a fire detection system, signals occupants to evacuate a premise. It is very important in large, multi-storey buildings where occupants may be unaware of fire in another part the building, and thus, is unlikely or impractical for warning to be provided. The capacity to identify the presence of fire is an essential component of a comprehensive fire detection strategy. We cannot inform inhabitants, trigger numerous other fire safety devices, or summon the fire department without a means of detection. If a flammable object comes in contact with oxygen and heat, fire can ignite quickly spreading to nearby goods [23]. As it grows, it become more intense in open space [24], [25]. In a close environ, fire can grow it is intensity until everything in it is path is consumed. It can also burn at a steady rate depending on the amount of oxygen [26]–[29]. Kizilkaya *et al.* [30] extended Kong *et al.* [31] to conclude that fire poses a grave threat with a record high of over 64,000 deaths reported annually between 2000 and 2019. It is financial impact resulted from losses estimated at over 1-trillion dollars worldwide, regardless of whether lives are lost [32], [33]. This damage can be extensive, with the severity of the fire determining the extent of the destruction. Direct losses may include property damage, sprinkler activation, firefighting expenses, falling debris, and structural damage and the indirect costs may result from repair time and temporary or permanent relocation [34]–[36].

To reduce fire hazards, Li *et al.* [37] must consider the time spent between fire detection and alert of all requisite authorities. Early detection is critical to ensure fire remains controllable. Fire detection at it is infancy is an effective instrument for saving lives and minimizing property damage. It is imperative to incorporate a scheme to detect a fire incident at it is incipient stage. When emergencies occur, lives can be saved and properties damage reduced by promptly providing information on quick and safe evacuation routes [38], [39]. Fire can be mitigated via IoT. IoT integration in resolving fire challenge will help yield accurate detection systems with real-time monitor and crisis management [40]. Smart homes direct their attention today, to IoT as means to streamline monitoring, tracing, communication, and management activities. It leverages on IoT's heterogeneity, real-time analytics, interoperability, distributed computing and linked tags to enable automated supply monitoring, and to achieve optimal results in data processing activities [41], [42]. We thus, presents a fire detection and alert ensemble that leverages IoT to identify fire in real-time and at it is earliest stages using a network of connected devices, sensors, software, and other technologies that enable seamless communication via the internet.

## 2. MATERIALS AND METHODS

### 2.1. Fire monitor and detection

A fire detection system yields an automatic mode to detect fire and alert [43], [44] residents of fire threat using either an audible or visual alarm that signals the evacuation of the occupants. This is critical in large or multi-storey buildings where occupants may be unaware of fire outbreak within the structure, and it is likely point of origin. It is ability to identify fire and it is source, is very essential as a fire detection strategy. The scheme should also trigger other fire safety measures and devices as well as inform inhabitants, and/or summon the fire department [45], [46]. While, humans can excellently detect fire since we can feel it is heat, perceive it is flames and smoke it is often not a dependable mode as we may not be available and at a variety of point within a building. Thus, we leverage on technology as means to monitor the radiation spectrum that our eyes cannot observe effectively. Thus, we explore the IoT's capacity to detect a range of spectrum via devices with photovoltaic, solid-state, or ionized gas tube components that respond to such spectrum(s). Electromagnetic signals at infrared, visible, or ultraviolet wavelengths can be recognized using flame detection systems [47].

Fire protection is the application of science and engineering principles aimed at protecting people, properties and the environment from a devastating fire. From ancient times, people have realized that early detection of fire has a positive effect in fire control. Development of fire detection technology was introduced due to a series of loss of lives and property damage [48], [49]. However, growth in fire detection scheme has been substantial over the last decade because of advances in sensors, data technologies, a greater understanding of fire physics, and new fire detection technologies and concepts developed over the last 2 decades [50].

## 2.2. Existing IoT-based detection ensemble

The proposed system extends [51] with priority to monitor indoor spaces with early detection that seeks to prevent potential danger. Existing model consists of 5-components: a gateway, an action point, an end device, a server and a user as in Figure 1. Careful analysis of the experimental framework is [52]–[55] and these includes; i) the end device with detection algorithm is equipped with sensors to measure gas, smoke, temperature, and humidity (indoors) monitoring the various levels of temperature, humidity, carbon monoxide, and smoke. Data collected via sensors are used to compute the probability of fire occurrence via a fuzzy system. With initialized room condition data, the fuzzy values are transmitted to the gateway via XBee comms. The detection algorithm then considers the temperature, humidity, smoke, and carbon monoxide inputs to generate probability output representing the likelihood of a fire. The rule-system assigns member-functions of low, medium, and high to each input; and, normal, fire, and alert to each output [56].




Figure 1. Block diagram of the existing system [51]

This approach enhances its accuracy and reliability while reducing the number of false alarms a user receives. The output via the transmission algorithm determines if (or not) the probability of fire as output and sends to it gateway via XBee communication. This decision is based on the classification of the fuzzy output of normal, fire, and alert; ii) the gateway is composed of a Raspberry Pi, XBee comm, and buzzer alarm. Sensor data from the end device is sent to a server via the XBee. If fire probability value from obtained data is categorized as alert, the gateway switches on the alarm to alert residents. If the probability value is categorized as fire, the gateway continuously rings and transmits a command broadcast to the action point to unlock the door as well as trigger other alarms. However, the buzzer does nothing if the condition is normal. The server helps store the data both in the cloud and on the user access media [57].

To ease user access, the system uses the Android app as a primary medium to help users connect via gateway using either the server, or directly to the gateway (if user is on the same local network). When the fire probability rises to the level of alert or fire, the server sends an alert to the application through cloud messaging to inform the user; and iii) the action point consists of an Arduino board, XBee module, and solenoid door lock (whose initial state is locked). There are 3 modes to unlock an action point by changing its status. First, is to unlock the door via a user command on app. All action points are opened for 5 seconds, and returns to a locked state. Secondly, when a user touches the action point unlock button, this hybrid mode unlocks the doors; and lastly, when the fire probability enters a FIRE class, this unlocks the action point until the level of fire decreases.

Our design prioritizes early intervention by monitoring the environment and employing safety measures to avert potential harm. It combines sensor, fuzzy logic, transmission algorithms, and cloud databases to ensure accuracy and reduce false alarms. Its interface eases users' access to data and alerts with action point to unlock the doors on a need-basis.

## 2.3. Experimental procedure for fire monitor, detection and alert (FiMoDeAL) scheme

It involves both hardware and software parts as in Figure 2. To efficiently and effectively detect any fire outbreaks, alert her occupants, and call the fire department emergency contact via twilio the ensemble

consists of the sensors (flame, MQ-2, temperature, and gas). Each of which is designed to detect the various elements of change in the instance of fire as well as a variety of gas concentration (for LPG, propane, methane, and smoke). It then uses the WiFi, which acts like a transmitter to send the received data for analysis by the Node MCU. It also fuses a Node MCU (ESP8285) controller with a buzzer, and LCD for seamless operation [58]–[60]. With the data acquired therein as input and sent to the ESP8285 the ensemble retrieves its threshold values and analyses them via comparison against the input values received from the sensors in real-time. It provides accurate data and alerts to residents and fire-fighting facilities. Divided into 2 segments based on its function to both provide a real time data cum alert residents, and a cloud-app that interacts directly with the fire department emergency contact [61]–[63].




Figure 2. Block diagram of the experimental ensemble (FiMoDeAL)

Ensemble effectively detects fire outbreaks instantaneously via the ESP8285 and its sensors to ensure residents are alerted in real-time, and fire department notified of the emergency. This system is a testament to the power of technology in ensuring public safety [64], [65]. To ensure fast-response of the system, all sensors and other components are connected via the Node MCU to detect fire or flame within 760–1,100 nanometres wavelength. This ensures that indoor data generated via the wireless sensors, are sent within the fastest time possible [66]. Furthermore, the Node MCU analyses all data, and compares it to its output with set threshold to determine the fire outbreak probability. With set parameters exceeding those of the predetermined threshold value(s), it indicates the existence of fire. The ensemble then further alerts residents and via the cloud-app (API), it computes the nearest fire service department using the Algorithm 1 to alert the fire department in real-time to yield a reliable, efficient mode to detect indoor fire outbreak. Its use of the sensors and controller, will promptly alert residents in the event of a fire outbreak [67].

#### Algorithm 1. For FiMoDeAL

INPUT: Number of nodes, N; OUTPUT: Print distance, previous

```

1: Create vertex set D
2: For each vertex v in G Do
3:   distance[v] ← infinity
4:   previous[v] ← undefined
5:   add v to D; distance[source] ← 0
6: where D is not empty Do
7:   u ← in D with min_distance[v]
8:   remove u from D
9: For each neighbour v of u Do
10:  sum ← distance[u] + length(u, v)
11:  if sum < distance[v] then
12:    distance[v] ← sum;
13:    previous[v] ← u;
14: end For
15: return distance[ ], previous[ ]
  
```

### 3. FINDINGS AND DISCUSSION

#### 3.1. Performance evaluation and discussion

The shortest path algorithms include a single-path is between a single source or supply node and all other vertices and all-pair path which evaluates the shortest path between all vertices in a graph. This study

*FiMoDeAL: pilot study on shortest path heuristics in wireless sensor network ... (Maureen Ifeanyi Akazue)*

determines the chosen algorithm based on the features and needs of the program. While, the single-source yields fastest responses we compared the Dijkstra and Bellman's Ford to identify the shortest, most efficient path between any 2 nodes, and this agreed with [68]. Dijkstra was found to outperformed Bellman Ford in both (un) directed nodes with positive weights, with simulations and comparative analysis as in Table 1.

Table 1. Application response time with scalability results

Number of nodes	Bellman-Ford in (ms)	Dijkstra in (ms)
5	1,351	513
10	3,724	756
15	9,577	2,072

Dijkstra's algorithm takes time on a graph with edges  $|E|$  and vertices  $|V|$  in finding it is time complexity to yield  $O(|E|+|V| \text{ Log})$ , which agrees with [69]–[71]. Also, for the Bellman-Ford, the time required is  $O(|V| \times |E|)$ . We infer that the Bellman-Ford algorithm takes more time than the Dijkstra algorithm. Hence, the comparison shows that the Dijkstra algorithm is faster than the Bellman-ford algorithm. For the longest amount of nodes [72]–[74], the Dijkstra's algorithm yielded a 2,072 seconds response time; while the Bellman-Ford algorithm yielded a 9,577seconds response time for the same ensemble.

### 3.2. Temperature response

We installed the proposed experimental ensemble/device in a kitchen at an initial distance of 0.25-meters from the fire source, to investigate it is rate/speed of fire monitoring and detection. Table 1 shows the experiment conducted, placing the ensemble as varied distances from the fire-source so as to measure it is response time and fire detection capability. The response time is the time required to detect fire and notify the fire service department. If we varied the device at a variety of distances ranging at 0.25 m, 0.5 m, 0.75 m, 1.25 m, 1.5 m, 1.75 m, 2.0 m, 2.25 m, 2.5 m, 2.75 m, 3.0 m, and 3.25 m respective we retrieved a corresponding time response of 0.312 s, 1.014 s, 1.716 s, 2.418 s, 3.120 s, 3.822 s, 4.524 s, 5.226 s, 5.928 s, 6.630 s, 7.032 s, and 7.734 s respectively as in Table 1 – with its result in agreement with [75]. The ensemble detects fire accurately with response time that varies appropriately, according to it is distance from the source of fire as illustrated in Figure 3 [76], [77]. This wireless sensor network ensemble yielded several insights on functionality and performance. First, it yielded an accurate measure of environ. Second, ensemble effectively compared collected values with high level of accuracy in determining the fire source. Lastly, it efficiently alert residents and fire department to instill confidence and reliability as it is core functionality [78].

### 3.3. Flame response

Any flame sensor by design is instructed to detect light within a specific range of wavelengths allowing the sensor to observe and capture as input, light within the spectrum and threshold set. Studies identified 33 nm as the acceptable, allowable range to aid fast detection capability [79], [80] as a change in distance will cause a consequent change in the observed wavelength values, so that the greater the distance and increase in nm increase the less accurate the it is prediction/detection. And with a lesser accuracy yield is observed with an increased distanced between the sensor and the flame incident. As in Figure 3, for 2.5 cm the reading was detected and observed in a response time of 0.312 s. In 32.5 cm the reading was detected and observed in 7.734 s as in Figure 3.




Figure 3. Test result from fire detection testing

#### 4. CONCLUSION

Study models a fuzzy system that fuses sensors and ESP8285 controller to determine fire probability output. It sends an alert to users via a send algorithm having monitored environment conditions as they quickly change. Previous systems used were often found to have provided false alarms owing to their configuration logic. The experimental design that yielded the proposed ensemble however notifies both the residents and the nearest fire department of fire outbreak, source and location using a shortest distance algorithm. The proposed ensemble is efficient, reliable and can handle dynamic changes as in the send algorithm. Our goal was to integrate this ensemble onto existing components within residential facilities so as to effectively reduce the loss of life and properties. The increased use and adoption of machine learning approaches and a variety of other automated processes with industrial IoT technologies both on the home (residential) frontiers and industrial applications has continued to drive up the demand for adaptation of advanced flame detection solutions.

These detectors can be integrated into complex automation systems, enabling real-time monitoring, remote alerts, and automated response actions. These, we hope will be modified to help effectively manage the risks associated with fire as well as address other critical issues of needs therein. With IoT-based fire detection and sensing systems, sensors are placed as detection nodes with built-in interaction units. A key problem to be addressed for the future also is the issues of low-power, and fault tolerance. Many flame sensors have been found to yield high rate in false alarm due to it is infrared, visible, and ultraviolet radiation. Such interferences often caused by non-fire sources, should be compensated. Also, the EMI-and-RFI noises can also affect the performance of the sensor, so it needs to be studied. Fire detection and control is a complicated operation. Because of it is various phases, diverse appearance, colors, emission spectra, combustion fuel, and position, complexities arise. In these circumstances, using fuzzy logic and deep learning-based algorithms to improve the current fire detection system's performance could be beneficial. Optimization techniques need to be improved to minimize false alarms. After simultaneous interpreting, all data from various sensors must be processed and analyzed according to sensor fusion technology.

#### REFERENCES

- [1] W. Benzekri, A. El, O. Moussaoui, and M. Berrajaa, "Early Forest Fire Detection System using Wireless Sensor Network and Deep Learning," *Int. J. Adv. Comput. Sci. Appl.*, vol. 11, no. 5, 2020, doi: 10.14569/IJACSA.2020.0110564.
- [2] T. N. Boutsika and S. A. Papathanassiou, "Short-circuit calculations in networks with distributed generation," *Electr. Power Syst. Res.*, vol. 78, no. 7, pp. 1181–1191, Jul. 2008, doi: 10.1016/j.epsr.2007.10.003.
- [3] S. Arlati *et al.*, "Analysis for the design of a novel integrated framework for the return to work of wheelchair users," *Work*, vol. 61, no. 4, pp. 603–625, Jan. 2019, doi: 10.3233/WOR-182829.
- [4] S. Chiemeke and E. Omede, "Mal-typho diagnosis intelligent system (MATDIS): the auto-diagnostic rule generation algorithm," *Comput. Inf. Syst. Dev. Informatics Allied Res. J.*, vol. 5, no. 4, pp. 83–92, 2021.
- [5] K. Bouabdellah, H. Nouredine, and S. Larbi, "Using Wireless Sensor Networks for Reliable Forest Fires Detection," *Procedia Comput. Sci.*, vol. 19, pp. 794–801, 2013, doi: 10.1016/j.procs.2013.06.104.
- [6] F. O. Aghware, R. E. Yoro, P. O. Ejeh, C. C. Odiakao, F. U. Emordi, and A. A. Ojugo, "DeLClustE: Protecting Users from Credit-Card Fraud Transaction via the Deep-Learning Cluster Ensemble," *Int. J. Adv. Comput. Sci. Appl.*, vol. 14, no. 6, pp. 94–100, 2023, doi: 10.14569/IJACSA.2023.0140610.
- [7] I. Ehsan *et al.*, "Internet of Things-Based Fire Alarm Navigation System: A Fire-Rescue Department Perspective," *Mob. Inf. Syst.*, vol. 2022, pp. 1–15, Sep. 2022, doi: 10.1155/2022/3830372.
- [8] H. Al-Bashiri, M. A. Abdulgabbler, A. Romli, and F. Hujainah, "Collaborative Filtering Recommender System: Overview and Challenges," *Adv. Sci. Lett.*, vol. 23, no. 9, pp. 9045–9049, Sep. 2017, doi: 10.1166/asl.2017.10020.
- [9] H. Alqourabah, A. Muneer, and S. M. Fati, "A smart fire detection system using iot technology with automatic water sprinkler," *Int. J. Electr. Comput. Eng.*, vol. 11, no. 4, p. 2994, Aug. 2021, doi: 10.11591/ijece.v11i4.pp2994-3002.
- [10] J. A. Carlson, "The economics of fire protection: from the great fire London to rural/Metro1," *Econ. Aff.*, vol. 25, no. 3, pp. 39–44, Sep. 2005, doi: 10.1111/j.1468-0270.2005.00570.x.
- [11] A. Mukherjee, S. K. Shome, and P. Bhattacharjee, "Survey on Internet of Things Based Intelligent Wireless Sensor Network for Fire Detection System in Building," *Communication and Control for Robotic Systems*, 2022, pp. 193–200, doi: 10.1007/978-981-16-1777-5\_12.
- [12] A. H. Altowaijri, M. S. Alfaifi, T. A. Alshawi, A. B. Ibrahim, and S. A. Alshebeili, "A Privacy-Preserving Iot-Based Fire Detector," *IEEE Access*, vol. 9, pp. 51393–51402, 2021, doi: 10.1109/ACCESS.2021.3069588.
- [13] A. A. Ojugo, P. O. Ejeh, C. C. Odiakao, A. O. Eboka, and F. U. Emordi, "Predicting rainfall runoff in Southern Nigeria using a fused hybrid deep learning ensemble," *Int. J. Informatics Commun. Technol.*, vol. 13, no. 1, pp. 108–115, Apr. 2024, doi: 10.11591/ijict.v13i1.pp108-115.
- [14] C. L. Udeze, I. E. Eteng, and A. E. Ibor, "Application of Machine Learning and Resampling Techniques to Credit Card Fraud Detection," *J. Niger. Soc. Phys. Sci.*, vol. 12, p. 769, Aug. 2022, doi: 10.46481/jnsps.2022.769.
- [15] R. F. R. Suleiman and F. Q. M. I. Reza, "Gas Station Fuel Storage Tank Monitoring System using Internet of Things," *Int. J. Adv. Trends Comput. Sci. Eng.*, vol. 8, no. 1.6, pp. 531–535, Dec. 2019, doi: 10.30534/ijatcse/2019/7881.62019.
- [16] Y.-J. Kim, H. Kim, S. Lee, and W.-T. Kim, "Trustworthy Building Fire Detection Framework With Simulation-Based Learning," *IEEE Access*, vol. 9, pp. 55777–55789, 2021, doi: 10.1109/ACCESS.2021.3071552.
- [17] S. Saponara, A. Elhanashi, and A. Gagliardi, "Real-time video fire/smoke detection based on CNN in antifire surveillance systems," *J. Real-Time Image Process.*, vol. 18, no. 3, pp. 889–900, Jun. 2021, doi: 10.1007/s11554-020-01044-0.
- [18] A. A. Ojugo, P. O. Ejeh, C. C. Odiakao, A. O. Eboka, and F. U. Emordi, "Improved distribution and food safety for beef processing and management using a blockchain-tracer support framework," *Int. J. Informatics Commun. Technol.*, vol. 12, no. 3, p. 205, Dec. 2023, doi: 10.11591/ijict.v12i3.pp205-213.
- [19] M. El-Hosseini, H. ZainEldin, H. Arafat, and M. Badawy, "A fire detection model based on power-aware scheduling for IoT-






- sensors in smart cities with partial coverage," *J. Ambient Intell. Humaniz. Comput.*, vol. 12, no. 2, pp. 2629–2648, Feb. 2021, doi: 10.1007/s12652-020-02425-w.
- [20] R. Braddock and C. Chambers, "Tank gauging systems used for bulk storage of gasoline," *Inst. Chem. Eng. Symp. Ser.*, no. 156, pp. 553–559, 2011.
  - [21] J. I. Chang and C.-C. Lin, "A study of storage tank accidents," *J. Loss Prev. Process Ind.*, vol. 19, no. 1, pp. 51–59, Jan. 2006, doi: 10.1016/j.jlp.2005.05.015.
  - [22] P. A. Zawislak, F. M. Reichert, D. Barbieux, A. M. S. Avila, and N. Pufal, "The dynamic chain of innovation: bounded capabilities and complementarity in agribusiness," *J. Agribus. Dev. Emerg. Econ.*, vol. 23, pp. 1–113, Apr. 2022, doi: 10.1108/JADEE-04-2021-0096.
  - [23] J. Chin, V. Callaghan, and S. Ben Allouch, "The Internet-of-Things: Reflections on the past, present and future from a user-centered and smart environment perspective," *J. Ambient Intell. Smart Environ.*, vol. 11, no. 1, pp. 45–69, Jan. 2019, doi: 10.3233/AIS-180506.
  - [24] E. Omede and U. K. Okpeki, "Design and implementation of autotech resource sharing system for secondary schools in Delta State," *J. Niger. Assoc. Math. Phys.*, vol. 51, no. 5, pp. 325–337, 2023.
  - [25] U. K. Okpeki and E. Omede, "A framework for campus network using cluster virtualization and transmission rate management," *J. Niger. Assoc. Math. Phys.*, vol. 49, no. January, pp. 335–344, 2023.
  - [26] F. M. Firmando, A. R. Muslikh, and D. R. I. M. Setiadi, "Analyzing InceptionV3 and InceptionResNetV2 with Data Augmentation for Rice Leaf Disease Classification," *J. Futur. Artif. Intell. Technol.*, vol. 1, no. 1, pp. 37–48, 2024.
  - [27] F. Mustofa, A. N. Safriandono, A. R. Muslikh, and D. R. I. M. Setiadi, "Dataset and Feature Analysis for Diabetes Mellitus Classification using Random Forest," *J. Comput. Theor. Appl.*, vol. 1, no. 1, pp. 41–48, 2023, doi: 10.33633/jcta.v1i1.9190.
  - [28] S. B. Imanulloh, A. R. Muslikh, and D. R. I. M. Setiadi, "Plant Diseases Classification based Leaves Image using Convolutional Neural Network," *J. Comput. Theor. Appl.*, vol. 1, no. 1, pp. 1–10, Aug. 2023, doi: 10.33633/jcta.v1i1.8877.
  - [29] H. Durani, M. Sheth, M. Vaghasia, and S. Kotech, "Smart Automated Home Application using IoT with Blynk App," in *2018 Second International Conference on Inventive Communication and Computational Technologies (ICICCT)*, IEEE, Apr. 2018, pp. 393–397, doi: 10.1109/ICICCT.2018.8473224.
  - [30] B. Kizilkaya, E. Ever, H. Y. Yatbaz, and A. Yazici, "An Effective Forest Fire Detection Framework Using Heterogeneous Wireless Multimedia Sensor Networks," *ACM Trans. Multimed. Comput. Commun. Appl.*, vol. 18, no. 2, pp. 1–21, May 2022, doi: 10.1145/3473037.
  - [31] S. G. Kong, D. Jin, S. Li, and H. Kim, "Fast fire flame detection in surveillance video using logistic regression and temporal smoothing," *Fire Saf. J.*, vol. 79, pp. 37–43, Jan. 2016, doi: 10.1016/j.firesaf.2015.11.015.
  - [32] M. I. Akazue *et al.*, "Handling Transactional Data Features via Associative Rule Mining for Mobile Online Shopping Platforms," *Int. J. Adv. Comput. Sci. Appl.*, vol. 15, no. 3, pp. 530–538, 2024, doi: 10.14569/IJACSA.2024.0150354.
  - [33] B. Bengherbia, S. Chadli, M. O. Zmirli, and A. Toubal, "A MicroBlaze based WSN sink node using XBee transceiver," in *2016 8th International Conference on Modelling, Identification and Control (ICMIC)*, IEEE, Nov. 2016, pp. 831–834, doi: 10.1109/ICMIC.2016.7804229.
  - [34] D. R. I. M. Setiadi, G. A. Trisnapradika, W. Herowati, and H. M. M. Islam, "Analyzing Preprocessing Impact on Machine Learning Classifiers for Cryotherapy and Immunotherapy Dataset," *J. Futur. Artif. Intell. Technol.*, vol. 1, no. 1, pp. 1–16, 2024.
  - [35] F. S. Perilla, G. R. Villanueva, N. M. Cacanindin, and T. D. Palaoag, "Fire Safety and Alert System Using Arduino Sensors with IoT Integration," in *Proceedings of the 2018 7th International Conference on Software and Computer Applications*, New York, NY, USA: ACM, Feb. 2018, pp. 199–203, doi: 10.1145/3185089.3185121.
  - [36] C. N. Verdouw, J. Wolfert, A. J. M. Beulens, and A. Rialland, "Virtualization of food supply chains with the internet of things," *J. Food Eng.*, vol. 176, pp. 128–136, May 2016, doi: 10.1016/j.jfoodeng.2015.11.009.
  - [37] Y. Li, A. Wu, N. Dong, J. Han, and Z. Lu, "Smoke Recognition Based on Deep Transfer Learning and Lightweight Network," in *2019 Chinese Control Conference (CCC)*, IEEE, Jul. 2019, pp. 8617–8621, doi: 10.23919/ChiCC.2019.8865302.
  - [38] R. K. Kodali and S. Yerroju, "IoT based smart emergency response system for fire hazards," in *2017 3rd International Conference on Applied and Theoretical Computing and Communication Technology (iCATecT)*, IEEE, Dec. 2017, pp. 194–199, doi: 10.1109/ICATCCT.2017.8389132.
  - [39] N. N. Wijaya, D. R. I. M. Setiadi, and A. R. Muslikh, "Music-Genre Classification using Bidirectional Long Short-Term Memory and Mel-Frequency Cepstral Coefficients," *J. Comput. Theor. Appl.*, vol. 2, no. 1, pp. 13–26, 2024.
  - [40] S. S. S. Yamuna, and S. N. George, "An IoT based Active Building Surveillance System using Raspberry Pi and NodeMCU," *arXiv*, Jan. 2020, doi: 10.48550/arXiv.2001.11340.
  - [41] H.-H. Liu, R. Y. Chang, Y.-Y. Chen, and I.-K. Fu, "Sensor-Based Satellite IoT for Early Wildfire Detection," in *2021 IEEE Globecom Workshops (GC Wkshps)*, IEEE, Dec. 2021, pp. 1–6, doi: 10.1109/GCWkshps52748.2021.9682098.
  - [42] P. Marwedel, "Embedded System Design," *Springer Nat.*, vol. 23, no. 1, pp. 1–13, 2021, doi: 10.1007/978-3-030-60910-8.
  - [43] G. Roque and V. S. Padilla, "LPWAN Based IoT Surveillance System for Outdoor Fire Detection," *IEEE Access*, vol. 8, pp. 114900–114909, 2020, doi: 10.1109/ACCESS.2020.3003848.
  - [44] P. P. Ray, M. Mukherjee, and L. Shu, "Internet of Things for Disaster Management: State-of-the-Art and Prospects," *IEEE Access*, vol. 5, pp. 18818–18835, 2017, doi: 10.1109/ACCESS.2017.2752174.
  - [45] A. Imteaj, T. Rahman, M. K. Hossain, M. S. Alam, and S. A. Rahat, "An IoT based fire alarming and authentication system for workhouse using Raspberry Pi 3," in *2017 International Conference on Electrical, Computer and Communication Engineering (ECCE)*, IEEE, Feb. 2017, pp. 899–904, doi: 10.1109/ECACE.2017.7913031.
  - [46] W. H. W. Ismail, H. R. M. Husny, and N. Y. Abdullah, "Smoke Detection Alert System via Mobile Application," in *Proceedings of the 10th International Conference on Ubiquitous Information Management and Communication*, New York, NY, USA: ACM, Jan. 2016, pp. 1–6, doi: 10.1145/2857546.2857581.
  - [47] W.-L. Hsu, J.-Y. Jhuang, C.-S. Huang, C.-K. Liang, and Y.-C. Shiau, "Application of Internet of Things in a Kitchen Fire Prevention System," *Appl. Sci.*, vol. 9, no. 17, p. 3520, Aug. 2019, doi: 10.3390/app9173520.
  - [48] A. Jadon, M. Omama, A. Varshney, M. S. Ansari, and R. Sharma, "FireNet: A Specialized Lightweight Fire & Smoke Detection Model for Real-Time IoT Applications," *arXiv*, May 2019, doi: 10.48550/arXiv.1905.11922.
  - [49] J. John, K. Harikumar, J. Senthilnath, and S. Sundaram, "An Efficient Approach with Dynamic Multi-Swarm of UAVs for Forest Firefighting," *arXiv*, Nov. 2022, doi: 10.48550/arXiv.2211.01958.
  - [50] A. Gaur *et al.*, "Fire Sensing Technologies: A Review," *IEEE Sens. J.*, vol. 19, no. 9, pp. 3191–3202, May 2019, doi: 10.1109/ISEN.2019.2894665.
  - [51] F. A. Saputra, M. U. H. Al Rasyid, and B. A. Abiantoro, "Prototype of early fire detection system for home monitoring based on Wireless Sensor Network," in *2017 International Electronics Symposium on Engineering Technology and Applications (IES-*

- ETA), IEEE, Sep. 2017, pp. 39–44, doi: 10.1109/ELECSYM.2017.8240373.
- [52] R. Alakbarov and M. Hashimov, "Application and Security Issues of Internet of Things in Oil-Gas Industry," *Int. J. Educ. Manag. Eng.*, vol. 8, no. 6, pp. 24–36, Nov. 2018, doi: 10.5815/ijeme.2018.06.03.
- [53] S. K. Datta, M. A. Shaikh, S. N. Srihari, and M. Gao, "Soft-Attention Improves Skin Cancer Classification Performance," *arXiv*, May 2021, doi: 10.48550/arXiv.2105.03358.
- [54] C. Joshi, J. R. Aliaga, and D. R. Insua, "Insider Threat Modeling: An Adversarial Risk Analysis Approach," *IEEE Trans. Inf. Forensics Secur.*, vol. 16, pp. 1131–1142, 2021, doi: 10.1109/TIFS.2020.3029898.
- [55] K. Pradeepa and M. Parveen, "Solid State Technology 8060 A Survey on Routing Protocols With Security in Internet of Things A Survey on Routing Protocols With Security in Internet of Things," *Int. Virtual Conf. Emerg. Trends Comput.*, vol. 63, no. 4, pp. 38–111, 2020.
- [56] A. E. Ibor, F. A. Oladeji, O. B. Okunoye, and O. O. Ekabua, "Conceptualisation of Cyberattack prediction with deep learning," *Cybersecurity*, vol. 3, no. 1, p. 14, Dec. 2020, doi: 10.1186/s42400-020-00053-7.
- [57] D. R. I. M. Setiadi, S. Rustad, P. N. Andono, and G. F. Shidik, "Digital image steganography survey and investigation (goal, assessment, method, development, and dataset)," *Signal Processing*, vol. 206, p. 108908, May 2023, doi: 10.1016/j.sigpro.2022.108908.
- [58] Sarwar, Bajwa, Jamil, Ramzan, and Sarwar, "An Intelligent Fire Warning Application Using IoT and an Adaptive Neuro-Fuzzy Inference System," *Sensors*, vol. 19, no. 14, p. 3150, Jul. 2019, doi: 10.3390/s19143150.
- [59] D. A. Sungeetha and D. R. Sharma R, "Real Time Monitoring and Fire Detection using Internet of Things and Cloud based Drones," *J. Soft Comput. Paradig.*, vol. 2, no. 3, pp. 168–174, Jul. 2020, doi: 10.36548/jscp.2020.3.004.
- [60] S. Sendra, L. García, J. Lloret, I. Bosch, and R. Vega-Rodríguez, "LoRaWAN Network for Fire Monitoring in Rural Environments," *Electron.*, vol. 9, no. 3, p. 531, Mar. 2020, doi: 10.3390/electronics9030531.
- [61] G. Sathyakala, V. Kirthika, and B. Aishwarya, "Computer Vision Based Fire Detection with a Video Alert System," in *2018 Int. Conf. Commun. Signal Process. (ICCSP)*, IEEE, Apr. 2018, pp. 0725–0727, doi: 10.1109/ICCSP.2018.8524216.
- [62] A. Sharma, P. K. Singh, and Y. Kumar, "An integrated fire detection system using IoT and image processing technique for smart cities," *Sustain. Cities Soc.*, vol. 61, p. 102332, Oct. 2020, doi: 10.1016/j.scs.2020.102332.
- [63] A. Shahraki, D. K. Kaffash, and O. Haugen, "A Review on the effects of IoT and Smart Cities Technologies on Urbanism," in *2018 South-Eastern Eur. Des. Autom. Comput. Eng. Comput. Networks Soc. Media Conf. (SEEDA-CECNSM)*, IEEE, Sep. 2018, pp. 1–8, doi: 10.23919/SEEDA-CECNSM.2018.8544932.
- [64] P. K. Singh and A. Sharma, "An insight to forest fire detection techniques using wireless sensor networks," in *2017 4th Int. Conf. Signal Process. Comput. Control (ISPCC)*, IEEE, Sep. 2017, pp. 647–653, doi: 10.1109/ISPCC.2017.8269757.
- [65] T. Sutikno, M. H. Ar-Rasyid, T. Wahono, and W. Arsadiando, "Internet of things with NodeMCU ESP8266 for MPX-5700AP sensor-based LPG pressure monitoring," *Int. J. Adv. Appl. Sci.*, vol. 12, no. 3, p. 257, Sep. 2023, doi: 10.11591/ijaas.v12.i3.pp257-264.
- [66] J. T. Eghwerido, L. C. Nzei, and F. I. Agu, "The Alpha Power Gompertz Distribution: Characterization, Properties, and Applications," *Sankhya A Indian J. Stat.*, vol. 83, no. 1, pp. 449–475, Feb. 2021, doi: 10.1007/s13171-020-00198-0.
- [67] S. Zhang, D. Gao, H. Lin, and Q. Sun, "Wildfire Detection Using Sound Spectrum Analysis Based on the Internet of Things," *Sensors*, vol. 19, no. 23, p. 5093, Nov. 2019, doi: 10.3390/s19235093.
- [68] R. A. Hasan, M. M. Akawee, and T. Sutikno, "Improved GIS-T model for finding the shortest paths in graphs," *Babylonian J. Mach. Learn.*, vol. 2023, pp. 17–26, 2023, doi: 10.58496/BJML/2023/002.
- [69] C. Abernathy, "Face Recognition Policy Development Template for Use in Criminal Intelligence and Investigative Activities," 2021. [Online]. Available: [www.it.ojp.gov](http://www.it.ojp.gov)
- [70] N. Tomar and A. K. Manjhar, "A Survey on Data Mining Optimization Techniques," *IJSTE-International J. Sci. Technol. Eng.*, vol. 2, no. 06, pp. 130–133, 2015.
- [71] A. Shoeibi et al., "Detection of epileptic seizures on EEG signals using ANFIS classifier, autoencoders and fuzzy entropies," *Biomed. Signal Process. Control*, vol. 73, pp. 1–18, 2022, doi: 10.1016/j.bspc.2021.103417.
- [72] A. E. Ibor, M. Hooper, C. Maple, and G. Epiphaniou, "Trustworthy Cross-Border Interoperable Identity System for Developing Countries," *arXiv*, Oct. 2023, doi: 10.48550/arXiv.2310.16562.
- [73] D. R. I. M. Setiadi and J. Jumanto, "An Enhanced LSB-Image Steganography Using the Hybrid Canny-Sobel Edge Detection," *Cybern. Inf. Technol.*, vol. 18, no. 2, pp. 74–88, Jun. 2018, doi: 10.2478/cait-2018-0029.
- [74] O. S. Eghwerido, P. O. Obasi, A. Tahirou, and M. Ojide, "Analysis of the profitability of maize product in Nigeria," *FUPRE J. Sci. Ind. Res.*, vol. 8, no. 2, pp. 80–94, 2024.
- [75] E. B. Wijayanti, D. R. I. M. Setiadi, and B. H. Setyoko, "Dataset Analysis and Feature Characteristics to Predict Rice Production based on eXtreme Gradient Boosting," *J. Comput. Theor. Appl.*, vol. 2, no. 1, pp. 79–90, 2024, doi: 10.62411/jcta.10057.
- [76] J. Figueiredo, M. A. Botto, and M. Rijo, "SCADA system with predictive controller applied to irrigation canals," *Control Eng. Pract.*, vol. 21, no. 6, pp. 870–886, Jun. 2013, doi: 10.1016/j.conengprac.2013.01.008.
- [77] S. R. Guntur, R. R. Gorrepati, and V. R. Dirisala, "Internet of Medical Things," *Med. Big Data Internet Med. Things*, no. February, pp. 271–297, Oct. 2018, doi: 10.1201/9781351030380-11.
- [78] B. O. Malasowe, M. I. Akazue, E. A. Okpako, F. O. Aghware, D. V. Ojie, and A. A. Ojugo, "Adaptive Learner-CBT with Secured Fault-Tolerant and Resumption Capability for Nigerian Universities," *Int. J. Adv. Comput. Sci. Appl.*, vol. 14, no. 8, pp. 135–142, 2023, doi: 10.14569/IJACSA.2023.0140816.
- [79] D. R. Ignatius, M. Setiadi, D. Marutho, and N. A. Setiyanto, "Comprehensive Exploration of Machine and Deep Learning Classification Methods for Aspect-Based Sentiment Analysis with Latent Dirichlet Allocation Topic Modeling," *J. Futur. Artif. Intell. Technol.*, vol. 1, no. 1, pp. 12–22, 2024, doi: 10.62411/faith.2024-3.
- [80] A. Onyan, D. Onyishi, T. Ebirebi, and R. Onawharaye, "Development of an IoT-based wireless remote health monitoring device," *FUPRE J. Sci. Ind. Res.*, vol. 8, no. 2, pp. 1–11, 2024.






## BIOGRAPHIES OF AUTHORS






**Maureen Ifeanyi Akazue**    received her M.Sc. Information Science in 2001 from the University of Ibadan, Nigeria, M.Sc. Computer Science in 2008 and Ph.D. Computer Science in 2014, both from the University of Benin, Nigeria. She currently lectures with the Department of Computer Science at the Delta State University, Abraka, Delta State, Nigeria. Her research interests are HCI, Online fraud prevention modeling, IoT, trust model, cyber security, and e-commerce. She is a member of The Nigerian Computer Society and Computer Professionals of Nigeria. She can be contacted at email: akazue@delsu.edu.ng.






**Abel Efetobor Edje**    received his Ph.D. Computer Science in the year 2021 from the Universiti Teknologi Malaysia, Johor in Malaysia. M.Sc. Information Systems Management in 2010 and BSc. Network Computing in 2009 from Brunel University, West London, United Kingdom. He is current lectures as a Senior Lecturer in the Department of Computer Science, Delta State University (DELSU), Abraka, Delta State, Nigeria. His area of interest is cloud of things, IoT, artificial intelligent systems, and machining learning. He can be contacted at email: toboredje@gmail.com.






**Margaret Dumebi Okpor**    received her B.Sc. and M.Sc. in Computer Science from the University of Benin in Edo State in 1997 and 2014 respectively. She further proceeded to obtain her Ph.D. in Computer Science from the Ignatius Ajuru University of Education in Rivers State. She currently lectures with the Department of Computer Science at The Delta State University of Science and Technology Ozoro in Delta State; and here research interest(s) includes (but not limited to): machine intelligence, data science, and cybersecurity. She is a member of Nigerian Computer Society (NCS) and Council of Computer Professionals of Nigeria (CPN). She can be contacted at email: okpormd@dsust.edu.ng.






**Wilfred Adigwe**    received B.Eng. in Computer Science and Engineering in 2000 from the Enugu State University of Science and Technology; M.Sc. in Computer Science in 2010 from the Nnamdi Azikiwe University Awka; and Ph.D. in Computer Science in 2018 from the Nnamdi Azikiwe University Awka. He currently lectures with the Department of Computer Science at the Delta State University of Science and Technology Ozoro. His research interests and areas of specializations includes data communication, data science, cybersecurity, and machine learning. He is a member of Computer Professionals, Registration Council of Nigeria (CPN), Nigeria Computer Society (NCS), and Cyber Security Experts of Nigeria (CSEAN). He can be contacted at email: adigwew@dsust.edu.ng.






**Patrick Ogholuwaremi Ejeh**    received his HND in Computer Science from the Federal Polytechnic Auchi, Edo State in 2006; M.Sc. in Computer Science from Northumbria University, Newcastle, United Kingdom in 2010; And, his Ph.D. in Computer Science from Sunderland University, Sunderland, United Kingdom in 2017. He is currently a Lecturer with the Department of Computer Science at the Dennis Osadebey University, Asaba, Delta State. His research interests includes; artificial intelligence, knowledge management, data science, and internet of things. He is also a member Nigerian Computer Society and Higher Education Academic; United Kingdom. He can be contacted at email: patrick.ejeh@dou.edu.ng.






**Christopher Chukwufunaya Odiakaose**    received his B.Sc. from Enugu State University of Science and Technology, Enugu and is M.Sc. from the Federal University of Petroleum Resources Effurun in Delta State. He is currently a Research Assistant and undergoing his Doctoral Studies with the Department of Computer Science at the Federal University of Petroleum Resources Effurun in Delta State, Nigeria. He currently works as a Technologist at The Department of Electrical and Electronics Technology Education, School of Secondary Education at the Federal College of Education (Technical) Asaba. He has several publications to his credit and his interest is in big-data, machine learning approaches and user trust modeling. He can be contacted at email: osegalaxy@gmail.com.






**Arnold Adimabua Ojugo**    received his B.Sc., M.Sc., and Ph.D. in Computer Science in 2000, 2005, and 2013 from Imo State University Owerri, Nnamdi Azikiwe University Awka, and Ebonyi State University Abakiliki respectively. He is a Professor with the Department of Computer Science at The Federal University of Petroleum Resources Effurun with research interest(s) in: machine intelligence computing and data science, cybersecurity, and graphs. He has many publications, and a member of various editorial boards (to include): frontiers in big data and international journal of modern education in computer science. He is a member of Nigerian Computer Society, Computer Professionals of Nigeria, and International Association of Engineers. He can be contacted at email: ojugo.arnold@fupre.edu.ng.






**Edim Bassey Edim**    received his B.Sc. in Computer Science from University of Calabar in 2006 and M.Sc. in Forensic Computing from Coventry University, United Kingdom. He is currently a Research Assistant and undergoing his Doctoral studies with the Department of Computer Science at Nile University of Abuja. He currently lectures with the Department of Computer Science at the Faculty of Physical Sciences, University of Calabar, Calabar. His research interests include: cyber security, cloud computing, digital forensics, machine learning, and artificial intelligence. He can also be contacted at the email: edime@unical.edu.ng.



**Rita Erhovwo Ako**    received her B.Sc. Industrial Mathematics degree from Delta State University, Abraka, Delta State, Nigeria in 2000; M.Sc. Computer Science from the University of Ibadan, Oyo State, Nigeria in 2005; M.Sc. Internet, Computer and System Security and Ph.D. Computer Science from the University of Bradford, Bradford, United Kingdom in 2006 and 2013 respectively. She is currently a senior lecturer with the Department of Computer Science at The Federal University of Petroleum Resources Effurun. She has several publications to her credit with research interests in: artificial intelligence, cybersecurity, e-commerce, embedded systems, and risk management. She is a member of the Nigerian Computer Society. She can be contacted at email: ako.rita@fupre.edu.ng.



**Victor Ochuko Geteloma**    received his B.Sc. in Computer Science from the Federal University of Petroleum Resources Effurun, Delta State, Nigeria in 2015; M.Sc. in Computer Science in 2019 from the Covenant University, Ogun State. He currently lectures with the Department of Computer Science at the Federal University of Petroleum Resources Effurun. He has several publications to his credit. His research interests include: cyber security, cloud computing, e-government, technology adoption, and digital inclusion. He is a member of the Nigerian Computer Society. He can be contacted at email: geteloma.victor@fupre.edu.ng.